



SPECIFICATIONS:

Current Rating: 1A AC,DC
 Voltage Rating: 50V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20MΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66,UL94V-0(White)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	1.00	3.00	2.40	12P	11.00	13.00	12.40
3P	2.00	4.00	3.40	13P	12.00	14.00	13.40
4P	3.00	5.00	4.40	14P	13.00	15.00	14.40
5P	4.00	6.00	5.40	15P	14.00	16.00	15.40
6P	5.00	7.00	6.40	16P	15.00	17.00	16.40
7P	6.00	8.00	7.40	17P	16.00	18.00	17.40
8P	7.00	9.00	8.40	18P	17.00	19.00	18.40
9P	8.00	10.00	9.40	19P	18.00	20.00	19.40
10P	9.00	11.00	10.40	20P	19.00	21.00	20.40
11P	10.00	12.00	11.40				



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	8:1	1 of 1
Draw BY:	Approved :	
Moore	GONGYB	

Title :
1.00mm PITCH
HOUSING

General Tolerance	
x.x≤0.25	ANGLE±
x.xx≤0.20	
x.xxx≤0.15	

DRAW NO : **A1002HE-XP** REV **A0**

A0	NEW RELEASE	2013.04.11
REV	DESCRIPTION	DATE