



SPECIFICATIONS:
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	2.54	7.10	5.60	10P	22.86	27.38	25.92
4P	7.62	12.20	10.68	12P	27.94	32.46	31.00
6P	12.70	17.30	15.76	15P	35.56	41.08	38.62
8P	17.78	22.30	20.84	22P	53.34	58.86	56.40
9P	20.32	24.84	23.38				

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	5:1	1 of 1
Draw BY:	Approved :	
LIZQ	GONGYB	

Title :
2.54mm PITCH
HOUSING
 DRAW NO : **A2549HA-XP** REV **A0**

REV	DESCRIPTION	DATE	General Tolerance	ANGLE±
A0	NEW RELEEASE	2010.10.09	x.x≤0.25 x.xx≤0.20 x.xxx≤0.15	